

## Durable Vertical Ringlock System Scaffolding for Efficient Construction

Our Product Introduction

for more products please visit us on [bythaiscaffold.com](http://bythaiscaffold.com)

### Basic Information

- Place of Origin: China
- Brand Name: Bythai
- Model Number: BT03



### Product Specification

- Horizontal Adjustment:  $\leq \pm 3^\circ$
- Components: Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.
- Vertical Load Capacity:  $\geq 45\text{KN}$
- Max Height:  $\leq 30\text{m}$
- Warranty: 2 Years
- Joints: Double-locking
- Size: 48.3mm
- Safety Factor:  $\geq 4$
- Highlight: Vertical Ringlock System Scaffolding, Double locking Ringlock System Scaffolding, 48.3mm Ringlock System Scaffolding



### More Images



## Product Description

### Product Description:

#### Ringlock System Scaffolding

Ringlock System Scaffolding is a versatile and lightweight scaffolding system that provides stability and safety for construction projects of all sizes. It features a unique interlocking design that allows for quick and easy assembly, and its components are designed to meet the highest safety standards. Its components include vertical, horizontal, diagonal, brace, base plate, ladder, and other accessories. All of these components are constructed with high-quality materials to ensure a secure, stable structure.

The Ringlock formwork is designed for maximum strength and stability with a weight of  $\leq 30\text{kg/m}^2$ . It is also designed with a vertical adjustment of  $\leq \pm 3^\circ$  for accurate placement and horizontal adjustment of  $\leq \pm 3^\circ$  to ensure the secure and correct positioning of the components. All of the components are manufactured to meet the EN12810 & EN12811 standards for safety and reliability.

The Ringlock scaffolding system is the perfect solution for any construction project. Its durable and lightweight design ensures stability and safety, while its quick and easy assembly and adjustable components make it an ideal choice for any job.

### Technical Parameters:

Components	Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.
Safety Factor	$\geq 4$
Warranty	2 Years
Max Height	$\leq 30\text{m}$
Material	Q235 Steel
Joints	Double-locking
Horizontal Adjustment	$\leq \pm 3^\circ$
Standard	EN12810 & EN12811
Horizontal Load Capacity	$\geq 15\text{KN}$
Size	48.3mm

### Applications:

Bythai Ringlock System Scaffolding (Model Number: BT03) is a high-quality scaffolding solution that is designed to provide maximum support and stability for construction projects. Made of Hot-dip Galvanized metal, it offers superior corrosion resistance and durability. The Ringlock System Scaffolding has a Horizontal Adjustment of  $\leq \pm 3^\circ$ , Horizontal Load Capacity of  $\geq 15\text{KN}$  and its Max Height is  $\leq 30\text{m}$ . It also comes with a 2-year warranty.

The Bythai Ringlock System Scaffolding can be used for a variety of applications, including commercial and residential construction, formwork, and shoring. It is highly versatile and can be easily adjusted to fit the needs of any construction project. It is designed to provide support and stability for construction projects, while also allowing for easy access and use of construction materials.

The Bythai Ringlock System Scaffolding is the perfect solution for any construction project. It is strong, durable, and offers superior corrosion resistance, making it a great choice for any construction project. With its Horizontal Adjustment of  $\leq \pm 3^\circ$ , Horizontal Load Capacity of  $\geq 15\text{KN}$ , and Max Height of  $\leq 30\text{m}$ , the Bythai Ringlock System Scaffolding is perfect for any construction project.

### Customization:

#### Bythai Ringlock System Scaffolding

Model Number: BT03

Place of Origin: China

Max Height:  $\leq 30\text{m}$

Safety Factor:  $\geq 4$

Weight:  $\leq 30\text{kg/m}^2$

Material: Q235 Steel

Size: 48.3mm

Bythai offers high-end **Ringlock Scaffolding** and **Ringlock Andamios** with superior quality and professional service. Our **Ringlock Scaffolding System** is designed with a max height of  $\leq 30\text{m}$ , safety factor of  $\geq 4$ , weight of  $\leq 30\text{kg/m}^2$ , material of Q235 steel and size of 48.3mm.

### Packing and Shipping:

#### Ringlock System Scaffolding Packaging and Shipping:

The Ringlock System Scaffolding is safely packed and shipped to customers in a standard wooden box. The box is sealed with plastic wrap and is securely fastened with two straps to prevent shifting during transit. The box should be handled with care to avoid damaging the product. The box should also be stored in a dry and safe environment.

## FAQ:

Q: What is the Brand Name of the Ringlock System Scaffolding?

A: The Brand Name of the Ringlock System Scaffolding is Bythai.

Q: What is the Model Number of the Ringlock System Scaffolding?

A: The Model Number of the Ringlock System Scaffolding is BT03.

Q: Where is the Ringlock System Scaffolding produced?

A: The Ringlock System Scaffolding is produced in China.

Q: What are the characteristics of the Ringlock System Scaffolding?

A: The Ringlock System Scaffolding is known for its high strength and durability, and its ability to be used for a variety of applications.

Q: What are the benefits of using the Ringlock System Scaffolding?

A: The Ringlock System Scaffolding is easy to assemble and disassemble, and it is also lightweight and space-saving. It is also safe to use, as it meets all safety regulations.



**Bythai Scaffolding Co.,Ltd**



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China