

Max Height≤30m Ringlock System Scaffolding with Safety Factor≥4

Basic Information

Place of Origin: ChinaBrand Name: BythaiModel Number: BT03



Product Specification

• Safety Factor: ≥4

• Weight: ≤30kg/m2
 • Max Height: ≤30m

• Surface Treatment: Hot-dip Galvanized

• Warranty: 2 Years

• Standard: EN12810 & EN12811

Vertical Load Capacity: ≥45KN
 Horizontal Adjustment: ≤±3°

• Highlight: 30m Ringlock System Scaffolding,

Galvanized Ringlock System Scaffolding

Product Description:

Ringlock system scaffolding is made of Q235 steel, which has high strength and durability, and is certified by both EN12810 and EN12811. It is one of the most popular formwork and scaffolding systems in the world. The vertical adjustment of the scaffolding is up to $\pm 3^{\circ}$ and the safety factor is ≥ 4 . The double-locking joints provide extra stability, making it suitable for a variety of applications. The ringlock ledger, ringlock formwork and ringlock andamios are all included in the system, making it an all-in-one scaffolding system.

Features:

Product Name: Ringlock System Scaffolding

Vertical Load Capacity: ≥45KN

Joints: Double-locking
Vertical Adjustment: ≤±3°
Horizontal Adjustment: ≤±3°
Standard: EN12810 & EN12811

Keywords: Scaffolding Ringlock, Ringlock formwork, Ringlock andamios

Applications:

Bythai BT03 Ringlock System Scaffolding

Bythai BT03 Ringlock System Scaffolding is perfect for construction projects of any size. It is lightweight, with a weight of ≤30kg/m2, and features a hot-dip galvanized surface treatment. It is made up of components such as vertical, horizontal, diagonal, brace, base plate, ladder, and more, all with a size of 48.3mm and an adjustable horizontal angle of ≤±3°. This ringlock standard formwork is perfect for any construction project, offering a reliable and safe solution.

Customization:

Bythai BT03 Customized Ringlock System Scaffolding

Brand Name: Bythai
Model Number: BT03
Place of Origin: China
Horizontal Adjustment: ≤±3°
Vertical Load Capacity: ≥45KN
Vertical Adjustment: ≤±3°
Weight: <30kg/m2

Weight: ≤30kg/m2 Joints: Double-locking

The Bythai BT03 Ringlock System Scaffolding is a customized and reliable formwork solution that allows for precise and safe horizontal and vertical adjustments. It is made of double-locking joints, and is capable of bearing vertical loads of up to 45KN. Moreover, it has a weight of no more than 30kg/m2 and can be adjusted up to ±3°.

Support and Services:

Ringlock System Scaffolding Technical Support and Services

Ringlock System Scaffolding provides technical support and services to customers who have purchased our products. Our team of experienced professionals are here to help in any way they can, from troubleshooting technical issues to answering questions about product features and operations.

We offer phone and email support for all our products, and have a dedicated technical support team available 24/7. We can provide troubleshooting tips and advice, and can also help you find the right product for your needs.

We also provide training and installation services for our products. Our team can help you set up and install the system, and provide all the necessary training to get you up and running quickly.

At Ringlock System Scaffolding, we are committed to providing the best customer service possible. If you have any questions or need assistance, please don't hesitate to contact us.

Packing and Shipping:

Packaging and Shipping

Ringlock System Scaffolding is packaged and shipped in multiple packages, including a main frame, base clamps and accessories.

The main frame and base clamps will be wrapped in plastic and boxed for shipping.

Accessories will be bagged and boxed separately.

All packages will be labeled and marked with the Ringlock System Scaffolding name and part numbers.

Packages will be loaded onto pallets for shipping.



Bythai Scaffolding Co.,Ltd

17300780862

info@bythaiscaffolding.com

bythaiscaffold.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China