

Powder Coating Scaffold Steel Props Prop Jacks With Powder Finish

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: bythai
- Minimum Order Quantity: 1000
- Price: 4.5-8.5
- Delivery Time: 15-25
- Payment Terms: L/C



Product Specification

- Application: Construction
- Brand: Bythai
- Color: Silver
- Material: Steel
- Name: Adjustable Steel Prop
- Size: Adjustable
- Surface Treatment: Galvanized, Spray Plastic
- Type: Adjustable Steel Prop
- Highlight: **Powder Finish Scaffold Steel Props, Powder Coating Prop Jacks, Galvanized Scaffold Steel Props**



for more products please visit us on bythaiscaffold.com

Product Description

Scaffold Steel Props with Powder Coating High-Quality Prop Jacks with Powder Finish

product description:

Scaffolding steel supports are an essential construction tool used to provide support and stability to temporary work platforms and structures. Our range of scaffolding steel supports is renowned for its superior quality, diverse specifications and wide range of applications.

Specifications and dimensions:

Materials: We offer two main steel options including durable Q235 and strong Q355B.

Lengths: Our products are available in a variety of length options including 40mm, 48mm, 56mm, 60mm, 70mm, 76mm and 89mm to meet a variety of support needs.

Surface treatment: Customers can choose surface treatment of spraying process, galvanizing, pre-galvanizing or hot-dip galvanizing to adapt to different environments.





Performance features:

Our scaffolding steel supports offer outstanding performance features including:

- High load-bearing capacity to ensure the stability of the working platform.
- Corrosion resistance, suitable for different climate and environmental conditions.
- A variety of specifications to choose from to meet various engineering needs.

Maintenance and Care: Check for Corrosion and Damage: Regularly inspect support rods, threads, nuts and other components to ensure there is no corrosion, rust or obvious damage. If any problems are found, damaged parts should be repaired or replaced promptly.

Lubrication: Regularly lubricate threads and other moving parts of supports to ensure they operate smoothly. Use appropriate lubricants or greases to prevent wear and corrosion.

Avoid overuse: Scaffolding supports have a limited maximum load and range of use, and overuse should be avoided to reduce the risk of damage and accidents.

Storage and transportation: When not using supports, store in a dry, ventilated place protected from sunlight and rain. During transportation, be careful to avoid collision and damage.

Regular Inspections: Conduct comprehensive inspections on a regular basis to ensure the safety and availability of supports. If there are any problems, prompt measures should be taken to repair or replace damaged parts.

Quality Standards and Certifications:

Our scaffolding steel supports meet the highest quality standards in the industry and have obtained relevant quality certifications, providing customers with confidence and assurance.

Packaging and delivery:

Products are packed in containers to ensure safe delivery. Shipping

****Marketing Promotion:** Our products are widely exported to the Middle East, America, Africa and other markets.

With years of technological innovation and quality management, we have won the trust and praise of global customers.

Summarize:

Scaffolding steel supports are ideal for the construction and engineering sectors and our product range offers exceptional quality, varied specifications and multiple surface treatment options. No matter what type of support your project requires, we have a solution for you. We are committed to providing high quality, durable and reliable products to ensure your project is safe and successful. For more information, please contact us.

- Durability ensures long-term use and excellent performance.



Bythai Scaffolding Co.,Ltd



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China