


Strength Galvanised Scaffold Tubes 48.3mm EN39/BS1139 Steel Pipe

Our Product Introduction

for more products please visit us on bythaiscaffold.com


Basic Information

- Place of Origin: China
- Brand Name: Bythai Scaffolding
- Certification: SGS ISO
- Model Number: BT201
- Minimum Order Quantity: 1000
- Price: \$10-\$85
- Packaging Details: In bundles
- Delivery Time: 10-15 days
- Payment Terms: TT/TC
- Supply Ability: 1000tons per month



Product Specification

- Yield Strength: 245N/mm2
- Material: Galvanised Steel
- Name: Galvanised Scaffold Tube
- Tensile Strength: 420N/mm2
- Weight: 6.4kg/m
- Application: Scaffolding
- Surface Treatment: Galvanised
- Diameter: 48.3mm
- Highlight: **EN39/BS1139 galvanised scaffold tube,
48.3mm galvanised scaffold tube,
BS1139 galvanised scaffold tube**



Product Description

Product Description:

The Galvanised Scaffold Tube is designed to meet the EN39 standard, which means that it has been tested and approved for use in construction projects across Europe. This standard ensures that the scaffold tube is of the highest quality and meets all safety requirements.

The Galvanised Scaffold Tube also features a galvanized surface treatment, which provides an extra layer of protection against corrosion and rust. This treatment ensures that the scaffold tube will last for years without requiring any maintenance or repairs.

With a thickness of 3.2mm, the Galvanised Scaffold Tube is strong enough to support heavy loads and withstand the wear and tear of daily use. Its yield strength of 245N/mm² makes it suitable for use in a wide range of construction projects.

The Galvanised Scaffold Tube is also known as the galvanized scaffold tube 48, which refers to its external diameter of 48mm. This size is perfect for use in most construction projects and can be easily integrated into any scaffolding system.

In summary, the Galvanised Scaffold Tube is a high-quality product that is designed to meet the needs of any construction project. Its EN39 standard, galvanized surface treatment, thickness of 3.2mm, and yield strength of 245N/mm² make it the perfect choice for any scaffolding system that requires strength, durability, and reliability.

Technical Parameters:

Parameter	Value
Name	Galvanised Scaffold Tube
Material	Galvanised Steel
Surface Treatment	Galvanised
Diameter	48.3mm
Thickness	3.2mm
Weight	6.4kg/m
Yield Strength	245N/mm ²
Tensile Strength	420N/mm ²
Standard	EN39
Application	Scaffolding



Bythai Scaffolding Co.,Ltd

 17300780862

 info@bythaiscaffolding.com

 bythaiscaffolding.com

No. 605,Industrial Exchange Center ,Huanghua Town Changsha Hunan China