

## Tubular System trength Galvanised Steel Scaffold Tube 48.3mm OD 3.2mm EN39 Standard

Our Product Introduction

for more products please visit us on [bythaiscaffold.com](http://bythaiscaffold.com)

### Basic Information

- Place of Origin: China
- Brand Name: Bythai Scaffolding
- Certification: SGS ISO
- Model Number: BT201
- Minimum Order Quantity: 1000
- Price: \$10-\$85
- Packaging Details: In bundles
- Delivery Time: 10-15 days
- Payment Terms: TT/TC
- Supply Ability: 1000tons per month



### Product Specification

- Material: Galvanised Steel
- Diameter: 48.3mm
- Thickness: 3.2mm
- Weight: 6.4kg/m
- Standard: EN39
- Name: Galvanised Scaffold Tube
- Application: Scaffolding
- Yield Strength: 245N/mm<sup>2</sup>
- Highlight: **EN39 Galvanised Steel Scaffold Tube,  
3.2mm Galvanised Steel Scaffold Tube,  
48.3mm Galvanised Steel Scaffold Tube**



### More Images



## Product Description

### Features:

Product Name: Galvanised Scaffold Tube

Name: Galvanised Scaffold Tube

Diameter: 48.3mm

Yield Strength: 245N/mm<sup>2</sup>

Tensile Strength: 420N/mm<sup>2</sup>

Surface Treatment: Galvanised

Galvanised Scaffold Tube is a top-quality steel and pipe product designed to meet your scaffolding needs. With a diameter of 48.3mm, this tube is perfect for use in construction, repair, and maintenance projects. Its impressive yield strength of 245N/mm<sup>2</sup> and tensile strength of 420N/mm<sup>2</sup> make it a reliable, sturdy choice for any job. Additionally, its galvanised surface treatment ensures that it is resistant to rust and corrosion, making it a cost-effective and long-lasting solution. Contact us today to get the scaffolding tube price that best suits your budget. Our Galvanised Scaffold Tube meets BS1139 scaffolding tube standards, so you can trust that you're investing in a high-quality, durable product.

### Technical Parameters:

Application:	tube scaffolding
Weight:	6.4kg/m
Thickness:	3.2mm
Tensile Strength:	420N/mm <sup>2</sup>
Material:	Galvanised Steel
Surface Treatment:	Galvanised
Name:	Galvanised Scaffold Tube
Yield Strength:	245N/mm <sup>2</sup>
Diameter:	48.3mm
Standard:	EN39

### Applications:

The Galvanised Scaffold Tube has a model number of BT201 and is produced in China. The minimum order quantity for this product is 1000, and the price ranges from \$10-\$85. The packaging details for this product are in bundles, and the delivery time is 10-15 days.

Payment terms for this product include TT/TC, and the supply ability is 1000 tons per month.

As its name implies, the Galvanised Scaffold Tube is primarily used for scaffolding. This tube has a diameter of 48.3mm, which is the standard diameter for tube scaffolding in the industry. Its tensile strength is 420N/mm<sup>2</sup>, which makes it suitable for use in heavy-duty applications.

This product is ideal for use in construction sites, building maintenance, and other scenarios that require a stable and safe scaffolding system. The Galvanised Scaffold Tube is also suitable for use in residential and commercial projects that require temporary access or support structures. Its galvanised surface treatment ensures that it is resistant to rust and corrosion, making it suitable for outdoor use. The Galvanised Scaffold Tube meets the BS1139 scaffolding tube standard, which ensures its compatibility with other scaffolding components. This product is easy to assemble and disassemble, making it ideal for temporary structures.



**Bythai Scaffolding Co.,Ltd**



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China